


## SL192326-TB-XL-BR

### Cylindrical roller bearing

Schaeffler Kimliği:  
0535305510000

Cylindrical roller bearing SL1923, full compl, roller set self-retaining, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type SL19

### Teknik bilgiler



### Dimensions

$D_1$	227,9 mm	Shoulder diameter outer ring
$D_{a \max}$	227,5 mm	Maximum diameter of housing shoulder
$d_1$	176 mm	Shoulder diameter inner ring
$d_{a \min}$	157,5 mm	Minimum diameter shaft shoulder
$d_{c \min}$	176 mm	Minimum shaft shoulder
F	157,9 mm	Raceway diameter inner ring
$r_{a \max}$	4 mm	Maximum fillet radius
$r_{\min}$	4 mm	Minimum chamfer dimension
s	5 mm	Axial displacement
	27,8 kg	Ağırlık

### Main Dimensions & Performance Data

d	130 mm	Bore diameter
D	280 mm	Outside diameter
B	93 mm	Width
$C_r$	1.260.000 N	Basic dynamic load rating, radial
$C_{0r}$	1.380.000 N	Basic static load rating, radial
$C_{ur}$	225.000 N	Fatigue load limit, radial
$n_G$	1.810 1/min	Limiting speed
$n_{gr}$	1.040 1/min	Reference speed

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.