


SL192348-TB-BR

Cylindrical roller bearing

Schaeffler Kimliği:
0547121650000

Cylindrical roller bearing SL1923, full compl, roller set self-retaining, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type SL19

Teknik bilgiler



Dimensions

D_1	408,5 mm	Shoulder diameter outer ring
$D_{a \max}$	408,5 mm	Maximum diameter of housing shoulder
d_1	312,5 mm	Shoulder diameter inner ring
$d_{a \min}$	280,5 mm	Minimum diameter shaft shoulder
$d_{c \min}$	312,5 mm	Minimum shaft shoulder
F	280,6 mm	Raceway diameter inner ring
$r_{a \max}$	5 mm	Maximum fillet radius
r_{\min}	5 mm	Minimum chamfer dimension
s	10 mm	Axial displacement
	141,61 kg	Ağırlık

Main Dimensions & Performance Data

d	240 mm	Bore diameter
D	500 mm	Outside diameter
B	155 mm	Width
C_r	2.900.000 N	Basic dynamic load rating, radial
C_{0r}	3.800.000 N	Basic static load rating, radial
C_{ur}	390.000 N	Fatigue load limit, radial
n_G	860 1/min	Limiting speed
n_{gr}	500 1/min	Reference speed

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.